


NOTES:

1. ELECTRICAL: 20KW (+/-10%), 480 VOLTS 3-PHASE WITH DOWNSTREAM RTD/PT100 (or TC) INDEPENDENT MEDIUM SENSOR ALL WETTED PARTS WILL BE 316 STAINLESS STEEL
2. PART TESTED TO 80 PSI AT 20-25C
3. TEMP TESTED ~100C EACH ZONE
4. ASSEMBLY CLEANED TO BCE SPEC UT-19
5. MUST PASS 700VDC, 0.5mA, 5 SECONDS PRIOR TO SHIP

<p>The information given herein is based on data believed to be accurate, but BCE makes no expressed or implied warranties as to its accuracy and assumes no liability arising out of its use by others. This information does not constitute a license to use or infringe on any patents</p>	UNLESS OTHERWISE SPECIFIED:		PART. NO.	
	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ±.005 THREE PLACE DECIMAL ±.001		 TITLE:	
	INTERPRET GEOMETRIC TOLERANCING PER:		<h2 style="margin: 0;">Mega Clean Flow Heater - Large DI Water</h2>	
	MATERIAL	SEE DWG	SIZE	DWG. NO.
FINISH	N/A	A	BCE11253	-
DO NOT SCALE DRAWING		SCALE: NTS	WEIGHT: N/A	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELLOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELLOVE CO. ENGINEERS IS PROHIBITED.